







Dimensions and ratings are subject to change without notice. Available in all insulation thickness.

## Note:

• For welded anchor, see: C2000

For small bore welded tee"no moment" anchor, see: C1100

For insulated friction anchor, see: C3000For insulated positive anchor, see: C4000

				Insulation Thickness						
Pipe				1"	2"	3"	4"	5"	6"	7"
Size	Α	F	G	В	В	В	В	В	В	В
8	6	12	0.38	4	4	6	6	8	8	10
10	6	12	0.38	4	4	6	6	8	8	10
12	6	12	0.38	4	4	6	6	8	8	10
14	6	12	0.38	4	4	6	6	8	8	10
16	6	12	0.38	4	6	6	8	8	10	10
18	9	18	0.5	4	6	6	8	8	10	10
20	9	18	0.5	4	6	6	8	8	10	10
24	9	18	0.5	4	6	6	8	8	10	10
30	12	18	0.5	4	6	6	8	8	10	10

## Application:

Model C2100 and C2130 are designed for use on:  $\cdot$  Pipe Sizes through 8" through 30"

Model No.	For use with Pipe Material
C2100	Carbon Steel
C2110	Chrome-Moly
C2120	Carbon Silicon
C2130	Stainless

## Features:

- Supplied with bolt holes for choice of bolting or welding to support structure.
- · Bottom-of-pipe to top-of-steel matches base mounted insulated supports. See "B" Series.
- · Broad selection of materials to match pipe material and eliminate galvanic action.

## Material Data:

- · C2100: A36 Carbon Steel.
- C2110: A387 Gr. 11 Chrome-Moly Steel.
- · C2120: A515 Gr. 70 Carbon Silicon Steel.
- · C2130: 304L Stainless Steel.
- **Primer Coating:** Primer coated or hot dipped galvanized. Other coatings available upon request.

Other materials available upon request.

Formal submittal sheets available