



Pipe Size	Maximum Lateral Load - Lbs.
3/4	50
1	50
1-1/4	50
1-1/2	50
2	50
2-1/2	50
3	50
3-1/2	50
4	50
5	50
6	50
8	50
10	50
12	50

TABLE I

Copper Tubing O.D.	Maximum Lateral Load - Lbs.
1-1/8	50
1-3/8	50
1-5/8	50
2-1/8	50
2-5/8	50
3-1/8	50
3-5/8	50
4-1/8	50

TABLE II

Contact factory for pipe sizes not shown.

Note: For neoprene lined clamps, see: G1000; For bolt-on clamps, see: G2200; For U-bolts, see: G3000

Framing Channel sold separately.

Application:

- Model G1200 is designed for use on:
- Hot water
 - Cold water
 - Chilled water
 - Dual temperature
 - Air
 - Gas
 - Vacuum

- Intended for installation on:
- Standard 1-5/8" width Framing Channels

Features:

- Easy installation
- Rugged
- Fits standard 1-5/8" width framing channel
- Sized to clamp on O.D. of bare pipe or bare copper tubing
- Vibration isolator
- Complete with top bolt and nut
- Other sizes available on request
- Neoprene sleeve eliminates galvanic action between clamp, framing channel and copper tubing.

Material Data:

- **G1200:** Applicable PSI specification document: No. 208.
- **Steel A:** Galvanized Steel 11 ga. X 1-1/4 wide ASTMA-653
- **Fasteners:** ASTMA-307 Plated.
- **Sleeve:** 1/4" thick X 2" wide closed cell neoprene..

Formal submittal sheets available